

Covinax 081-00

PRODUCT DESCRIPTION

Covinax 081-00 is a pressure sensitive, vinyl acrylic copolymer stabilized with a cellulosic colloid. The performance of this pressure sensitive emulsion is characterized by moderate peel adhesion, high shear resistance, and good quick tack. COVINAX 081-00 is thixotropic and has excellent mechanical stability. COVINAX 081-00 exhibits excellent adhesion to Mylar and cellophane.

PHYSICAL PROPERTIES

Polymer Type: Vinyl Acrylic Freeze/Thaw Stability: Unstable Protective System: Anionic/Cellulosic Weight per Gallon (lbs): 8.4
Viscosity (cps): 100 - 800 (LVF, Spindle #3/60RPM/77°F) Borax Compatible: Yes

Percent Solids: 52% - 55% Surface Tension: 33 dynes/cm.

pH: 4.2 – 5.2 **Shelf Life:** 6 months

ADDITIONAL INFORMATION

A 1 mil $(28g/M^2)$ dry film of Covinax 081-00 cast directly onto 1 mil thickness polyester film will exhibit the following average performance properties when tested on #304 stainless steel, which has a #3 surface finish.

Test180° Peel ¹
178° Shear ²
Loop Tack³

Performance Values

2.0 pounds 700 minutes 1.8 pounds

FDA Compliance: 21 CFR 175.105 21 CFR 176.180

IMPORTANT NOTICE TO CUSTOMER:

The recommendations and data contained in this Product Data Sheet for use of this product are based on information Franklin believes to be reliable. They are offered in good faith without guarantee, as conditions and methods of use of our product by Customer are beyond Franklin's control. Customer must determine the suitability of the product for a particular application before adopting it on a commercial scale.

All orders for Franklin products shall be subject to Franklin International, Inc.'s Standard Terms and Conditions of Sale which may be found at http://www.franklini.com/Terms and Conditions.aspx ("Standard Terms"). Different or additional terms proposed by Customer are expressly rejected and shall not become part of the agreement between Customer and Franklin International, Inc. with respect to any order. Contact Franklin International, Inc. immediately if you cannot access our Standard Terms and we will provide you a copy upon request. Any sale of products by Franklin to Customer is expressly conditional upon Customer's consent to the Standard Terms, and Customer's acceptance of any performance by, or receipt of products from, Franklin International, Inc. shall constitute Customer's acceptance of the Standard Terms and Conditions of Sale.

© Copyright 2012. All rights reserved. Franklin International. Revised 10/12/12.



¹Franklin International 03QC5002, 30 minute dwell

²Franklin International 03QC5003, 0.25 square inch, 500 gram load

³Franklin International 03QC5004, 1 square inch contact, 1 second dwell